


| SPECIFICATION | CONNECTION | BIPOLAR |
|--|------------|--------------------------------|
| AMPS/PHASE | | 4.24 |
| RESISTANCE/PHASE(Ohms)@25°C | | 0.70±10% |
| INDUCTANCE/PHASE(mH)@1KHz | | 3.00±20% |
| HOLDING TORQUE(Nm)[lb-in] | | 4.00[35.40] |
| STEP ANGLE(°) | | 1.80 |
| STEP ACCURACY(NON-ACCUM) | | ±5.00% |
| LEAD STYLE | | FVR 4X0.5mm ² CABLE |
| LIFE(h) | | 6000 |
| TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED) | | |
| AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F] | | |
| INSULATION RESISTANCE 100 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY) | | |
| INSULATION CLASS B 130°C[266°F] | | |
| DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE) | | |
| AMBIENT HUMIDITY MAX.85%(NO CONDENSATION) | | |

| TYPE OF CONNECTION (EXTERN) | | MOTOR | |
|-----------------------------|---------|-------|---------|
| PIN NO | BIPOLAR | LEADS | WINDING |
| 1 | A — | RED | |
| 2 | C — | GRN | |
| 3 | B — | YEL | |
| 4 | D — | BLU | |

| BRAKE SPECIFICATIONS | |
|--|----------------------|
| VOLTAGE | 24 |
| POWER | 11.5 |
| STATIC FRICTION TORQUE(Nm) | 2 |
| MOMENT of INTERIA(kg.cm ²) | 3.8x10 ⁻⁶ |
| MAX. SPEED(rpm) | 5000 |



| | | |
|-------|-----------|-----------|
| APVD | | 8.20.2018 |
| CHKD | | |
| 1:1.5 | DRN | |
| SCALE | SIGNATURE | DATE |

STEPPER MOTOR

24HS39-4204D-B200