



SPECIFICATION	CONNECTION	UNIPOLAR	BIPOLAR
AMPS/PHASE		2.00	1.40
RESISTANCE/PHASE(Ohms)@25°C		2.20±10%	4.40±10%
INDUCTANCE/PHASE(mH)@1KHz		7.00±20%	28.00±20%
HOLDING TORQUE(Nm)[lb-in]		2.20[19.47]	3.05[26.99]
STEP ANGLE(°)		1.80	
STEP ACCURACY(NON-ACCUM)		±5.00%	
ROTOR INERTIA(g-cm ²)		1400.00	
WEIGHT(Kg)[lb]		1.70[3.75]	
TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED)			
AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F]			
INSULATION RESISTANCE 100 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY)			
INSULATION CLASS B 130°C[266°F]			
DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE)			
AMBIENT HUMIDITY MAX.85%(NO CONDENSATION)			

STEP	A	B	\bar{A}	\bar{B}	O(\bar{O})	CW
1	+	+			+	
2		+	+		+	
3			+	+	+	
4	+			+	+	
1	+	+			+	

UNIPOLAR



BIPOLAR SERIES



STEPPERONLINE®

APVD		5.18.2022
CHKD		
1:1.5	DRN	
SCALE	SIGNATURE	DATE

STEPPER MOTOR

34HS26-2006D