


| SPECIFICATION  | CONNECTION | BIPOLAR     |
|--|------------|-------------|
| AMPS/PHASE   |            | 6.00        |
| RESISTANCE/PHASE(Ohms)@20°C  |            | 0.48±10%    |
| INDUCTANCE/PHASE(mH)@1KHz  |            | 3.50±20%    |
| HOLDING TORQUE(Nm)[lb-in]  |            | 4.80[42.52] |
| STEP ANGLE(°)  |            | 1.80        |
| STEP ACCURACY(NON-ACCUM)   |            | ±5.00%      |
| ROTOR INERTIA(g-cm²)   |            | —           |
| WEIGHT(Kg)[lb]   |            | —           |
| TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED)                |            |             |
| INSULATION RESISTANCE 100 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY)           |            |             |
| AMBIENT TEMPERATURE -20°C~50°C[-4°F~122°F]                                       |            |             |
| INSULATION CLASS B 130°C[266°F]  |            |             |
| DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE) |            |             |

| TYPE OF CONNECTION (EXTERN) |         | MOTOR |         |
|-----------------------------|---------|-------|---------|
| PIN NO                      | BIPOLAR | LEADS | WINDING |
| 1                           | A+ —    | BLK   |         |
| 2                           | A- —    | GRN   |         |
| 3                           | B+ —    | RED   |         |
| 4                           | B- —    | BLU   |         |

FULL STEP 2 PHASE-Ex ,  
WHEN FACING MOUNTING END (X)

| STEP | A+ | B+ | A- | B- | CW | CCW |
|------|----|----|----|----|----|-----|
| 1    | +  | +  | -  | -  | ↓  | ↑   |
| 2    | -  | +  | +  | -  |    |     |
| 3    | -  | -  | +  | +  | ↑  | ↓   |
| 4    | +  | -  | -  | +  |    |     |



**STEPPERONLINE®**

|       |           |            |
|-------|-----------|------------|
| APVD  |           | 12.18.2020 |
| CHKD  |           |            |
| 2:3   | DRN       |            |
| SCALE | SIGNATURE | DATE       |

**STEPPER MOTOR**

**34HS31-6004S1**