


SPEZIFIKATION	VERBINDUNG	BIPOLAR
AMPS/PHASE		0.30
RESISTANCE/PHASE(Ohms)@25°C		40.00±10%
INDUCTANCE/PHASE(mH)@1KHz		18.00±20%
HOLDING TORQUE(Nm)[lb-in]		0.03[0.27]
STEP ANGLE(°)		1.80
STEP ACCURACY(NON-ACCUM)		±5.00%
ROTOR INERTIA(g-cm ²)		4.00
WEIGHT(Kg)[lb]		0.08[0.18]
TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED)		
AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F]		
INSULATION RESISTANCE 100 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY)		
INSULATION CLASS B 130°C[266°F]		
DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE)		
AMBIENT HUMIDITY MAX.85%(NO CONDENSATION)		

TYPE OF CONNECTION (EXTERN)		MOTOR	
PIN NO	BIPOLAR	LEADS	WINDING
1	A —	BLK	A
2	A\ —	GRN	A\
3	B —	RED	B
4	B\ —	BLU	B\

FULL STEP 2 PHASE-Ex. ,
WHEN FACING MOUNTING END (X)

STEP	A	B	A\	B\		CCW
1	+	+	-	-	↓ ↑	↑ ↓
2	-	+	+	-		
3	-	-	+	+		
4	+	-	-	+		



APVD		8.17.2018
CHKD		
2:1	DRN	
RAHMEN	UNTERSCHRIFT	DATUM

SCHRITTMOTOR

8HS15-0304S