



SPECIFICATION	CONNECTION	BIPOLAR
AMPS/PHASE		0.24
RESISTANCE/PHASE(Ohms)@25°C		20.40±10%
MINIMAL THRUST(N)@300 PPS		39.00
LEAD(mm)		0.6096
LINEAR TRAVEL/STEP(mm)		0.003048
STEP ANGLE(°)		1.80
STEP ACCURACY(NON-ACCUM)		±5.00%
WEIGHT(Kg)[lb]		—
AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F]		
INSULATION RESISTANCE 20 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY)		
INSULATION CLASS B 130°C[266°F]		

PIN NO	TYPE OF CONNECTION (EXTERN)		MOTOR	
	BIPOLAR	LEADS	LEADS	WINDING
1	A+ —	RED	RED	A+
2	A- —	RED/WHT	RED/WHT	A-
3	B+ —	GRN	GRN	B+
4	B- —	GRN/WHT	GRN/WHT	B-

FULL STEP 2 PHASE-Ex. ,
WHEN FACING MOUNTING END (X)

CW	→			
A+	+		-	
A-	-		+	
B+		-		+
B-		+		-
CCW	←			



APVD	LDJ	12.18.2023
CHKD		
1.5:1	DRN	ZPJ
SCALE	SIGNATURE	DATE

STEPPER MOTOR
8E11S0244CC3-150RS