


REV.	REVISION RECORD	BY	DATE
0	ORIGIN	LDJ	3.31.2025



SPECIFICATION	CONNECTION	VALUE
GEAR RATIO		20
EFFICIENCY		94%
BACKLASH@NO-LOAD(arcmin)		<=20
MAX.PERMISSIBLE TORQUE(Nm)[lb-in]		12.00[106.21]
MOMENT PERMISSIBLE TORQUE(Nm)[lb-in]		24.00[212.42]
SHAFT MAXIMUM AXIAL LOAD(N)		100
SHAFT MAXIMUM RADIAL LOAD(N)		300
GEARBOX MATCHING MOTOR'S INPUT SHAFT LENGTH (mm)		MAX26.5
RATED INPUT SPEED(RPM)		3000
MAX. INPUT SPEED(RPM)		6000
NOISE(dB)		<=55
WATERPROOF RATING		IP54
LIFE(h)		20000
WORKING TEMPERATURE		-20°C~150°C[-4°F~302°F]

DIMENSIONS ARE IN MILLIMETERS.
TOLERANCES AS BELOW:
DECIMALS ANGLES
X ±0.5 ±2°
X.X ±0.25
X.XX ±0.13

THIRD ANGLE PROJECTION
SIGNATURE DATE

DRN LDJ 3.31.2025
APVD MYX 3.31.2025

STEPPERONLINE®

GEARBOX

TG40-G20

REV.	1	SCALE	2:3	DWG NO.	A4354
------	---	-------	-----	---------	-------