


| SPECIFICATION | CONNECTION | BIPOLAR |
|--|------------|----------|
| AMPS/PHASE | | 0.42 |
| RESISTANCE/PHASE(Ohms)@25°C | | 11.4±10% |
| INDUCTANCE/PHASE(mH)@1KHz | | 6.00±20% |
| MINIMAL THRUST(N)@300 PPS | | 57.00 |
| LEAD(mm) | | 0.635 |
| LINEAR TRAVEL/STEP(mm) | | 0.003175 |
| STEP ANGLE(°) | | 1.80 |
| STEP ACCURACY(NON-ACCUM) | | ±5.00% |
| LEAD TYPE | | AWG 26 |
| TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED) | | |
| AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F] | | |
| INSULATION RESISTANCE 100 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY) | | |
| INSULATION CLASS B 130°C[266°F] | | |
| DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE) | | |
| AMBIENT HUMIDITY MAX.85%(NO CONDENSATION) | | |

| TYPE OF CONNECTION (EXTERN) | | MOTOR | |
|-----------------------------|---------|---------|---------|
| PIN NO | BIPOLAR | LEADS | WINDING |
| 1 | A — | RED | |
| 2 | A\ — | RED/WHT | |
| 3 | B — | GRN/WHT | |
| 4 | B\ — | GRN | |

FULL STEP 2 PHASE-Ex. ,
WHEN FACING MOUNTING END (X)

| STEP | A | B | A\ | B\ | | CCW |
|------|---|---|----|----|---|-----|
| 1 | + | + | - | - | ↓ | ↑ |
| 2 | - | + | + | - | | |
| 3 | - | - | + | + | ↑ | ↓ |
| 4 | + | - | - | + | | |



STEPPERONLINE®

| | | | |
|-------|-----------|--|------------|
| | APVD | | 10.19.2021 |
| | CHKD | | |
| 1:1 | DRN | | |
| SCALE | SIGNATURE | | DATE |

STEPPER MOTOR

11N13S0424ED-150RS
(11LS13-04247-150N)