



The red mark is the positive pole

SPECIFICATION	CONNECTION	VALUE
RATED VOLTAGE(V);		24
NO LOAD CURRENT(mA);		≤200
NO LOAD SPEED(RPM);		125±13
RATED LOAD TORQUE(kgf.cm);		7
RATED CURRENT(mA);		≤1200
RATED LOAD SPEED(RPM);		100±10
STALL CURRENT(mA);		—
STALL TORQUE(kgf.cm);		—
ROTATION DIRECTION		CW/CCW

NOTES:

- 1.THE LEAD WIRE OF BIG MOTOR CAN NOT BE PULLED FORCIBLY TO AVOID INTERNAL POOR CONDUCTIVITY.
- 2.PREVENT GEAR MOTOR FROM BEING SHOCKED OR DROPPING IN MOUNTING PROCESS.IT IS PROHIBITED TO STRIKE AND CRUSH DIRECTLY ON REDUCER OUTPUT SHAFT.
- 3.IT IS NECESSARY TO BE CAREFUL THAT THE ADHESIVE DOES NOT SPREAD ALONG THE SHAFT AND FLOW INTO THE BEARING.
- 4.DO NOT TURN A GEARED MOTOR BY ITS OUTPUT SHAFT WHEN,FOR EXAMPLE,ARRANGING ITS POSITION SO AS TO INSTALL IT.
- 5.USE WITH A LOAD THAT EXCEEDS THE RATED TORQUE WILL BE REDUCE THE LIFETIME OF GEAR MOTOR.
- 6.CHECK MOTOR RUNNING WHEN IT IS POWER ON BEFORE INSTALLATION AND MAKE SURE PERFORMANCE MEET REQUEST .



	APVD		9.29.2022
	CHKD		
1:1	DRN		
SCALE	SIGNATURE		DATE

DC GEARBOX MOTOR

FGF-36244500-G36