



SPECIFICATION	CONNECTION	VALUE
RATED VOLTAGE(V);		24
NO LOAD CURRENT(mA);		≤600
NO LOAD SPEED(RPM);		326±33
RATED LOAD TORQUE(kgf.cm);		5
RATED CURRENT(mA);		≤3500
RATED LOAD SPEED(RPM);		245±24
STALL CURRENT(mA);		—
STALL TORQUE(kgf.cm);		—
ROTATION DIRECTION		CW/CCW

NOTES:

- PLEASE CONDUCT THE WELDING WORK IN A SHORT TIME.(RECOMMENDATION:WITH THE SOLDERING IRON TIP AT A TEMPERATURE OF 340~400℃, WITHIN 2 SECONDS.
- PREVENT GEAR MOTOR FROM BEING SHOCKED OR DROPPING IN MOUNTING PROCESS.IT IS PROHIBITED TO STRIKE AND CRUSH DIRECTLY ON REDUCER OUTPUT SHAFT.
- INSTALL THE SCREWS AFTER FIRST CHECKING THE TAPS AND TAP DEPTH AGAINST THE DIMENSIONS ENTERED ON THE EXTERIOR DRAWING.
- IT IS NECESSARY TO BE CAREFUL THAT THE ADHESIVE DOES NOT SPREAD ALONG THE SHAFT AND FLOW INTO THE BEARING.
- DO NOT TURN A GEARED MOTOR BY ITS OUTPUT SHAFT WHEN, FOR EXAMPLE, ARRANGING ITS POSITION SO AS TO INSTALL IT.

STEPPERONLINE®

	APVD	9.29.2022
	CHKD	
1:1	DRN	
SCALE	SIGNATURE	DATE

DC GEARBOX MOTOR

SGD51-43244500-G14