



SPECIFICATION	CONNECTION	VALUE
RATED VOLTAGE(V);		12
NO LOAD CURRENT(mA);		≤ 60
NO LOAD SPEED(RPM);		17.6 ± 2
RATED LOAD TORQUE(kgf.cm);		5
RATED CURRENT(mA);		≤ 250
RATED LOAD SPEED(RPM);		14 ± 1.4
STALL CURRENT(mA);		—
STALL TORQUE(kgf.cm);		—
ROTATION DIRECTION		CW/CCW

NOTES:

- PLEASE CONDUCT THE WELDING WORK IN A SHORT TIME.(RECOMMENDATION:WITH THE SOLDERING IRON TIP AT A TEMPERATURE OF $340 \sim 400^{\circ}\text{C}$, WITHIN 2 SECONDS.
- PREVENT GEAR MOTOR FROM BEING SHOCKED OR DROPPING IN MOUNTING PROCESS.IT IS PROHIBITED TO STRIKE AND CRUSH DIRECTLY ON REDUCER OUTPUT SHAFT.
- INSTALL THE SCREWS AFTER FIRST CHECKING THE TAPS AND TAP DEPTH AGAINST THE DIMENSIONS ENTERED ON THE EXTERIOR DRAWING.
- IT IS NECESSARY TO BE CAREFUL THAT THE ADHESIVE DOES NOT SPREAD ALONG THE SHAFT AND FLOW INTO THE BEARING.
- DO NOT TURN A GEARED MOTOR BY ITS OUTPUT SHAFT WHEN, FOR EXAMPLE, ARRANGING ITS POSITION SO AS TO INSTALL IT.

STEPPERONLINE®

	APVD		9.29.2022
	CHKD		
1:1	DRN		
SCALE	SIGNATURE		DATE

DC GEARBOX MOTOR

SGF25-24126000-G340